



**PRO-SW3000XLS**  
**SWING GATE OPERATOR**

For swing gates up to 16 ft. (4.9 m) long and 650 lbs. (294.8 kg) per leaf.



## XLS IMPROVEMENTS

- Reintroduction of product
- Increased operating speed by 10%
- NEW rev-counter board with reed switch technology (backward compatible)
- IMPROVED front mount and scraper seal design



Available From:

[www.gtoaccess.com](http://www.gtoaccess.com)



Intertek  
03/26/2015



Includes battery backup, radio receiver, entry transmitter, AC transformer and all necessary mounting hardware for a post mounted installation, 16" (40.6 cm) total offset.

## PRO-SW3000XLS

### SWING GATE OPERATOR

### RESIDENTIAL SERIES

The PRO-SW3000XLS/3200XLS series will operate a gate up to 16 ft. (4.9 m) long and weighing 650 lbs. (294.8 kg) each leaf if all proper installation procedures have been followed. Ball bearing hinges should be used on all gates weighing over 250 lbs. (113.4 kg).

#### FEATURES:

- One button auto-memorization of digital transmitter code.
- Includes battery backup, 318 MHz radio receiver, entry transmitter, AC transformer and all necessary mounting hardware for a post mounted installation, 16" (40.6 cm) total offset.

#### MECHANICAL:

- The GTO® control board can be programmed for pull-to-open or push-to-open.
- Operating temp -5 F (-21C) to +160 F (71 C).
- Opening time: From 15 to 18 seconds.
- Range of arm stroke: is up to 16" (41 cm).
- Operator length: with arm fully retracted is 40.25" (102 cm), mounting point to mounting point.
- Operation, diagnostic and safety alarms.
- Inherent obstruction sensing.
- Soft start/soft stop—for long mechanical life expectancy.
- Auto close adjustable 3–120 seconds delay.

#### ELECTRICAL/POWER:

- 12 Volt DC / 7.0 amp hour, sealed, rechargeable battery (included). Battery charge is maintained by a 120V AC/60 Hz input, 18V AC, 40 VA. output, transformer rectified to 14V DC through control board
- Powered by a reliable 12 Volt (120 Watt) DC motor, 16:1 planetary gear drive system.
- Charging regulated circuit on control board. "Sleep draw" is 15 mA; "active draw" is 3 to 7 amps.

#### SHIPPING WEIGHT:

3000XLS Kit 39 lbs. (18 kg);  
3200XLS 28 lbs. (13 kg);  
Meets UPS shipping standards.

#### WARRANTY:

2 Year (RESIDENTIAL application)

#### CLASS OF OPERATION:

Class I

#### SAFETY LISTINGS:

System Certified with UL325 5th Edition safety standards, ETL listed.

#### OPTIONS:

**Solar Power:** For dual gates, we recommend a minimum of 10 watts. (*FM123*)

**Dual Gates:** The PRO-SW3200XLS works as a second gate operator when combined with a PRO-SW3000XLS. Includes 40 ft. (12.2m) power cable.

**Push to Open applications:** require one Push-to-Open bracket (*R4388*) per operator.

#### SUGGESTED ACCESSORIES:

- Automatic Gate Lock (*FM144*)
- Wireless Driveway Alarm (*R4450*)
- Transmitters (*RB741/RB742*)

[www.gtoaccess.com](http://www.gtoaccess.com)

GTO®, GTO/PRO®, Bulldog®, GTO Access Systems™, are trademarks of GTO Access Systems ("GTO") and are the exclusive property of GTO. All rights are reserved by GTO, and these marks may not be used in any form without the prior written permission of GTO. © 2015